

B15 Double Leaf Steel Door



AREAS OF USE

Steel solid doors can be used in internal areas.

CERTIFICATE OF CONFORMITY

B15 class fire door meets IMO and SOLAS requirements according to European MED Directive 2014/90/EU and USCG regulations.

PROPERTIES

Resistance to fire: B15 (36 minutes tested)

Resistance to sound: 32dB

Door is produced from steel sheets with sandwich insulation. 40 mm door leaf is available with trimlists for installation of surface laminate.

Door frame depth is 50-55mm.

DIMENSIONS

Max dimensions for a door clear opening: 2200 x 2100 mm (width x height)
It is possible to increase dimensions up to 15% in width and height (max 10% of total area)

Door weight: 32kg/m²

FINISHING

Standard door finish is powder or wet paint.

In addition stainless steel (brushed or polished), PVC covered steel and laminate or other non-combustible design finishes can be used.

EXTRAS

Door leaves can be equipped with rectangular, round or oblong vision panel. Vision panel is available in size up to 420 x 1710 mm (width x height).

Door can be also equipped with top panel, kick-out panel, ventilation grille, spy eye, finger protection gasket and drop down threshold.

The door can be fitted with different mechanical and electrical locks, door closer systems and automatic door operators. Panic escape devices, door control elements and recessed handles can be used.

X-ray protection up to 4mm lead equivalent is available.

For more information, please contact marine@tammer.ee

