

STÅLPROFIL CONCEPT SP 300

Stålprofilsystem SP 35000, SP 95000 – EI 60

Glazed door partition

Holder/Issued to**Stålprofil PK AB**

Kärrestrandsvägen 126, SE-451 76 Uddevalla, Sweden

Product description**STÅLPROFIL CONCEPT SP 300**

Stålprofilsystem SP 35000 and SP 95000, single leaf and double leaf door of steel or stainless steel without transom, max size BxH 1350x2300 mm (single leaf door) and 2400x2300 mm (double leaf door), EI 60.

Intended use

Fire separating, glazed door partitions for internal installation in buildings.

Trade name**STÅLPROFIL CONCEPT SP 300**

Stålprofilsystem SP 35000, SP 95000, SP 75000, SP 975000

Approval

The products comply with the requirements of Chapter 8, Section 4, item 2 of the Planning and Building Act (2010:900), in the respects and under the conditions specified in this type approval. The approval covers the parts of the Swedish National Board of Housing, Building and Planning's (Boverket's) regulations and general recommendations specified below:

Boverket's Building Regulations (BBR) (BFS 2011:6 as amended up to and including BFS 2024:5) ¹:

Fire resistance class EI 60

BBR 5:231

¹ May be applied to the extent stated in the transitional provisions of Boverket's regulations BFS 2024:14.

Associated documents

-

Control

The factory production control (FPC) shall be performed according to the control plan, document no. 4-4731-B, dated 2020-04-09, and be monitored by an independent inspection body.

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this type approval. Further the product shall be accompanied by a manufacturer's assurance, certifying that the product has been manufactured in accordance with the documents on which this type approval is based.

Manufacturer

Manufacturing shall be carried out by manufacturers approved by the holder, for whom a decision on production control has been issued in accordance with Chapter 8, Sections 22 and 23 of the Planning and Building Act (2010:900).

Marking

The products are to be marked at the factory. The marking consists of a sign, label or text on every product supplied and includes:

Information on Manufacturer

Product type designation

Consecutive manufacture no./date of production

Type approval number

Boverket's registered trade mark

RISE Accreditation number

Inspection body

Manufacturers name and production site and decision number

e.g. SP 35000

no./date

1132/93

†

1002

name or trade mark

Basis for approval

Report no. 846000.14/96.514 from Norges Branntekniske Laboratorium (SINTEF NBL).

Assessment no. 92R12348 A and B together with report no. P303862B and P403518 from SP Sveriges Tekniska Forskningsinstitut.

Report no. PG11221 and PGA10610 from DBI.

Report no. 12447A from warringtonfiregent.

Report no. LBO-950/17E and LBO-1046/17E from Gryfitlab.

Report no. 405085 and 405086 from warringtonfire.

Report no. EFR-16-G-004298, EFR-18-V-000298 and EFR-18-V-003890 from efectis france

Manufacturing instructions in accordance with document no. 4-4679-B, dated 2020-04-08.

Drawings as shown in the drawing list no. 4-4693-C, dated 2025-01-30.

Comments

Customised drawings for each specific building project shall be produced by the manufacturer.

This type approval supersedes the previous type approval with the same number dated 2020-05-13.

Validity

Valid up to and including 2029-07-01.

The validity of this type approval can be verified at RISE homepage.

The validity of this type approval expires when the type approved products with the intended use according to this type approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011 or 2024/3110.

A handwritten signature in blue ink, appearing to read "Stefan Coric".

Stefan Coric

This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish original shall take precedence.