

B-15 Glazed Automatic Sliding Door

MGF102 / MGF202 AUTOMATIC

AREAS OF USE

B-15 glazed automatic sliding doors combine fire protection, space-efficient operation, and easy access with openness, visibility, and natural light, making them particularly suitable for premium and high-revenue internal spaces.

PROPERTIES

Fire classification	B-15
Compliance	IMO / SOLAS / MED
Sound reduction	NPD
Application	Internal environments
Maximum clear opening (W x H), mm	Single leaf: 1200 x 2276 Double leaf: 2166 x 2276 Maximum dimensions may be increased for specific projects, subject to compliance with IMO MSC.1/Circ.1319.
Total weight	45 kg/m ²
Locking and function	Compatible with a range of electrical drive systems. The door is equipped with flush finger pulls for manual operation when the drive system is switched off and the door leaf needs to be moved manually. Various control and safety accessories are available to achieve the required functionality while maintaining fire and operational safety.
Extras	A wall pocket supporting frame with pre-prepared openings and matching service and maintenance hatches can be supplied to simplify installation and provide easy access to the drive system. Profile finishes include painted steel, brushed or polished stainless steel, and custom finishes. Glazing options include clear, satin, printed, mirror, and decorative glass, with printed patterns protected inside the glazing unit for improved scratch resistance. Custom glazing, profile finishes, color combinations, and other project-specific configurations are available on request. ADA-compliant configurations are also available.



STANDARD ASSEMBLY

Supplied with a door leaf and fire sealing list system, finished in standard RAL paint and fitted with clear fire-rated glass. Includes an electrical drive system, safety sensors, program selector, and activation switch.