

B-15 Glazed Door


MGF101 / MGF201

AREAS OF USE

B-15 glazed hinged doors are suitable for internal marine areas where fire protection is required while maintaining openness, visibility, and natural light, particularly in premium and high-revenue spaces.

PROPERTIES

Fire classification	B-15
Compliance	IMO / SOLAS / MED
Sound reduction	NPD
Application	Internal environments
Maximum clear opening (W x H), mm	Single leaf: 1060 x 2100 Double leaf: 1860 x 2100 Maximum dimensions may be increased for specific projects, subject to compliance with IMO MSC.1/Circ.1319.
Total weight	45 kg/m²
Locking and function	Compatible with a range of mechanical and electrical locks, including access control integration, as well as door closers, and automatic operators.
Extras	Options include various threshold options, transoms, and different profile shapes and widths. Available surface finishes include painted steel, brushed or polished stainless steel, and custom finishes. Glazing options include clear, satin, printed, mirror, and decorative glass. Custom glazing, profile finishes, ADA-compliant solutions, and other project-specific configurations are available on request.



STANDARD ASSEMBLY

Supplied with a door leaf and frame, finished with standard RAL powder coating, and including a standard mechanical lock compatible with DIN or TV key cylinders (cylinder is not included), escutcheons with lever handle, and a door closer.