

B15 Lightweight Manual Steel Sliding Door MSF102

AREAS OF USE

Steel lightweight sliding doors with or without glass can be used in internal areas.

CERTIFICATE OF CONFORMITY

B15 class fire door meets IMO and SOLAS requirements according to European MED Directive 2014/90/EU and USGC regulations.

PROPERTIES

Resistance to fire: B15 (37 minutes tested)

Door leaf is insulated and made from steel sheets with sandwich construction in thickness of 40mm. Door leaf edges are covered with trimlists.

Sliding door is manually operated and can be ordered with installation supporting frame for convenient and easy installation on site. Manual system is equipped with counterweight self-closing system.



DIMENSIONS

Max dimensions for a door clear opening: 1380 x 2200 mm (width x height)

It is possible to increase dimensions up to 15% in width and height (max 10% of total area)

Door weight: 32kg/m²

FINISHING

Standard door finish is powder or wet paint.

In addition stainless steel (brushed or polished), PVC covered steel and laminate or other non-combustible design finishes can be used.

EXTRAS

The door can be fitted with different mechanical lock systems and flush handles. For manually operated doors it is possible to add a lock case.

It is possible to add round or rectangular vision panel to the product.

Maximum dimensions for a rectangular vision panel clear opening: 400 x 600 mm (width x height). Maximum diameter for a round vision panel clear opening: 400 mm.