

Lightweight Metal Door SMU111

AREAS OF USE

An insulated lightweight metal door is intended for use in indoor conditions (basement, storage room and other indoor spaces) where high fire resistance and security are not required.

CONFORMITY

The door characteristics have been assessed in accordance with the requirements of standard EN 14351-2 (internal doors)

MEASUREMENTS AND PROPERTIES

Door frame depth: 62 mm

Door leaf thickness: 62 mm

Door set weight: 30 kg/m²

Material: Electro-galvanized steel sheet, 1.0 mm

Lightweight door is manufactured as a single-leaf door. The door is equipped with two metal door hinges, zinc-plated or stainless steel (zn or ss). In the standard solution, the hinges are not painted.

Doors can be ordered in the following modular sizes: 8×21, 9×21, 10×21.

For alternative dimensions, please consult the sales department.



FINISHING

Standard finish: RAL Classic colour range; smooth matte powder coating (35% gloss level).

Lightweight doors can be manufactured from PVC-coated steel sheet; however, this finish may result in a longer delivery time. Please consult the sales department to specify this solution.



EXTRAS

Locking options: ASSA 565 or EURO 1769 (factory-installed lock or lock preparation).

Door set options:

The door set can be ordered with a bent stainless steel threshold or without a threshold.

Hardware options:

Lock cylinder, handle and/or door closer can be supplied loose or factory-installed.